


In the Claims:

Claims 1-12, 13, 22, 23 and 26-29, cancel.

REMARKS

A Schedule of Amendments is submitted herewith. The above amendments are presented in order to place this application in better condition for examination.

Respectfully submitted,




John Smith-Hill
Reg. No. 27,730

SMITH-HILL & BEDELL, P.C.
12670 N.W. Barnes Road, Suite 104
Portland, Oregon 97229

Tel. (503) 574-3100
Fax (503) 574-3197

Certificate of Mailing

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231, on the 17th day of May, 2002.





COPY OF PAPER
ORIGINALLY FILED

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

David A. KRITLER et al

Art Unit: 1762

Application No: 10/055,165

Examiner:

Filed: January 21, 2002

For: APPARATUS AND METHOD FOR PREPARING
A COATED OPTICAL FIBER

SCHEDULE OF AMENDMENTS

Paragraphs [0013], [0015], [0016], and [0018], rewrite as follows:

[0013] (Amended) In accordance with a [fourth] first aspect of the invention there is provided a method of preparing a length segment of optical fiber, comprising employing a first gripping element to grip the length segment at a first location, employing a second gripping element to grip the length segment at a second location, spaced from the first location, urging the second gripping element away from the first gripping element, and employing a strain gauge to generate a strain gauge signal that depends on tension in the fiber between the first and second gripping elements.

[0015] (Amended) In accordance with a [sixth] second aspect of the invention there is provided apparatus for preparing a length segment of fiber, comprising a fiber guide for guiding a loose end segment of fiber in a direction transverse of its length towards a gripping location, and at least one gripping element at the gripping location for gripping the loose end segment, and wherein the fiber guide includes at least one wire member.

[0016] (Amended) In accordance with a [seventh] third aspect of the invention there is provided apparatus for cleaving a length segment of optical fiber, comprising a first clamp for gripping the length segment at a first location, a

second clamp for gripping the length segment at a second location, spaced from the first location, an actuator for urging the second clamp away from the first clamp to tension the fiber segment between the first and second clamps, a cleaving element, a translation means for moving the cleaving element between a first location, in which it is spaced from the fiber segment, and a second location, in which it contacts a fiber segment held under tension between the first and second clamps, and an acoustic means for vibrating the cleaving element and inducing a fracture in the fiber segment when the cleaving element is in the second location.

[0018] (Amended) In accordance with a [ninth] fourth aspect of the invention there is provided apparatus for preparing a length segment of optical fiber, comprising an intake means for receiving the length segment, a tool that acts on the length segment in preparing the length segment and, in so doing, creates fiber debris, a debris container, a duct leading from the vicinity of the tool to the debris container, and a vacuum pump connected to the container for inducing a flow of air through the duct for carrying fiber debris into the container.